

Danilo Automotive Private Limited

Plot No. 3 and 4, Chandulal Bowl, Secunderabad Containment,
Opp. Tadbund Hanuman Temple, Secunderabad - 500009,
Telangana - India. Mob. 95059 74049



TECHNICAL

DATA

SHEET

Multitech

TDI

15W40

MULTITECH TDI 15W40 is a top quality oil for gasoline or diesel turbo compressed or atmospheric engines of light vehicles and vans. Working at maximum power, it offers perfect services in the most severe conditions.

MULTITECH TDI 15W40 has been designed technologically to bring the following results:

- High thermal stability, allowing work at high temperatures.
- Superior quality. It facilitates the cold start of the engine and it improves the lubrication process in cold and hot temperatures.
- It prevents sludge formation and deposits. Low ash content.
- It prevents cylinder sleeve deterioration.
- Very resistant to tear and wear, it ensures a longer life span for engines.
- Superior antioxidant, anticorrosive, antirust and antifoaming power.
- High cleaning – dispersion capacity.

SAE Degree	15W40
Viscosity at 100°C	14.4 cSt.
Viscosity at 40°C	110 cSt.
Viscosity Index	135
Pour point	-27°C
Flash point	224°C
TBN	8.7 mg KOH/g

It complies with the norms:

API-SN/CH-4



100% Subsidiary of Danilo Automotive Holland, Ruychaverstraat 3 2013 GE HAARLEM
The Netherlands - EUROPE, M : +31(0)6 182 703 14 • E : info@daniloautomotive.com
W : www.daniloautomotive.com

Danilo Automotive Private Limited

Plot No. 3 and 4, Chandulal Bowl, Secunderabad Containment,
Opp. Tadbund Hanuman Temple, Secunderabad - 500009,
Telangana - India. Mob. 95059 74049



ACEA A2/B3

MB 229.1



100% Subsidiary of Danilo Automotive Holland, Ruychaverstraat 3 2013 GE HAARLEM
The Netherlands - EUROPE, M :+31(0)6 182 703 14 • E : info@daniloautomotive.com
W : www.daniloautomotive.com