

Danilo Automotive Private Limited

Plot No. 3 and 4, Chandulal Bowl, Secunderabad Containment,
Opp. Tadbund Hanuman Temple, Secunderabad - 500009,
Telangana - India. Mob. 95059 74049



TECHNICAL DATA SHEET

UNIVERSAL CAR 5W40 (FULLY SYNTHETIC)

UNIVERSAL CAR 5W40 is a high performance fully synthetic lubricant, which offers maximum efficiency and protection in the sector of automobile lubricants.

UNIVERSAL CAR 5W40 is formulated with the finest and most exclusive synthetic bases, outrunning the requirements of gasoline and Diesel engines, with or without turbo compressor, being specially recommended for competition engines, or for those having severe and intensive use. The final result is a lubricant that offers incomparable anti wear properties and gives the maximum effectiveness in a wide range of temperatures.

UNIVERSAL CAR 5W40 possesses some unique characteristics due to its synthetic formula, having the following characteristics:

- Perfect fluidity.
- Very low frost point.
- Maximum resistance at high temperatures.
- Maximum protection of the mechanic elements.
- High viscosity index.
- Low rubbing index.

| | |
|--------------------|-------------|
| SAE Classification | 5W40 |
| Viscosity at 100°C | 14.1 cSt |
| Viscosity at 40°C | 90 cSt |
| Index of viscosity | 162 |
| Pour point | - 50 °C |
| Flash point | 225 °C |
| TBN | 9.5 |

It complies with the norms:



100% Subsidiary of Danilo Automotive Holland, Ruychaverstraat 3 2013 GE HAARLEM
The Netherlands - EUROPE, M : +31(0)6 182 703 14 • E : info@daniloautomotive.com
W : www.daniloautomotive.com

Danilo Automotive Private Limited

Plot No. 3 and 4, Chandulal Bowl, Secunderabad Containment,
Opp. Tadbund Hanuman Temple, Secunderabad - 500009,
Telangana - India. Mob. 95059 74049



API SN/CF
ACEA A5/B5
MB 229.3/229.5



100% Subsidiary of Danilo Automotive Holland, Ruychaverstraat 3 2013 GE HAARLEM
The Netherlands - EUROPE, M : +31(0)6 182 703 14 • E : info@daniloautomotive.com
W : www.daniloautomotive.com